

Package ‘wnl’

August 27, 2020

Version 0.6.1

Title Minimization Tool for Pharmacokinetic-Pharmacodynamic Data Analysis

Description

This is a set of minimization tools (maximum likelihood estimation and least square fitting) to solve examples in the Johan Gabrielsson and Dan Weiner's book ``Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications'' 5th ed. (ISBN:9198299107). Examples include linear and nonlinear compartmental model, turn-over model, single or multiple dosing bolus/infusion/oral models, allometry, toxicokinetics, reversible metabolism, in-vitro/in-vivo extrapolation, enterohepatic circulation, metabolite modeling, Emax model, inhibitory model, tolerance model, oscillating response model, enantiomer interaction model, effect compartment model, drug-drug interaction model, receptor occupancy model, and rebound phenomena model.

Depends R (\geq 3.0.0), numDeriv

Author Kyun-Seop Bae [aut]

Maintainer Kyun-Seop Bae <k@acr.kr>

Copyright 2017-, Kyun-Seop Bae

License GPL-3

NeedsCompilation no

LazyLoad yes

Repository CRAN

URL <https://cran.r-project.org/package=wnl>

R topics documented:

wnl-package	2
cmpChi	3
Comp1	3
DAT	4
dx	5
ExpandDH	5
nComp	6
nlr	7
Secondary	9
SolComp2	10
SolComp3	10
wnl5	11

Index**13**

wnl-package	<i>Minimization Tool for Pharmacokinetic-Pharmacodynamic Data Analysis</i>
-------------	--

Description

This is a minimization tool to solve the examples in the book Gabrielsson J, Weiner D. 'Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications' 5th ed. 2016. (ISBN:9198299107).

Details

This is a set of minimization tools to solve all the examples in the book 'Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications' 5th ed. 2016.

Author(s)

Kyun-Seop Bae jk@acr.kr

References

Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.

Examples

```
tData = Theoph
colnames(tData) = c("ID", "BWT", "DOSE", "TIME", "DV")

fPK = function(THETA)      # Prediction function
{
  DOSE = 320000             # in microgram
  TIME = e$DATA[, "TIME"]   # use data in e$DATA

  K    = THETA[1]
  Ka   = THETA[2]
  V    = THETA[3]

  Cp   = DOSE/V*Ka/(Ka - K)*(exp(-K*TIME) - exp(-Ka*TIME))
  return(Cp)
}

IDs = unique(tData[, "ID"])
nID = length(IDs)
for (i in 1:nID) {
  Data = tData[tData$ID == IDs[i],]
  Res = nlr(fPK, Data, pNames=c("k", "ka", "V"), IE=c(0.1, 3, 500),
            SecNames=c("CL", "Thalf", "MRT"), SecForms=c(~V*k, ~log(2)/k, ~1/k))
  print(paste("## ID =", i, "##"))
  print(Res)
}
```

cmpChi	<i>Compare model with Chi-square test</i>
--------	---

Description

It performs chi-square test for two models comparison.

Usage

```
cmpChi(r1, r2)
```

Arguments

r1	A result from nlr
r2	Another result from nlr

Details

One model should include the other model.

Value

Returns a p-value from pchisq

Author(s)

Kyun-Seop Bae jsk@acr.kr.i

Comp1	<i>One compartment model - analytical</i>
-------	---

Description

It calculates using one compartment model.

Usage

```
Comp1(Ke, Ka=0, DH)
```

Arguments

Ke	Elimination rate constant
Ka	Absorption rate constant
DH	Expanded dosing history table

Details

First compartment is the gut compartment for oral dosing. IV bolus and infusion dosing should be done at the second compartment.

Value

This returns a table with the gut and the central compartment columns

Author(s)

Kyun-Seop Bae jsk@acr.kr

Examples

```
DAT
DAT2 = ExpandDH(DAT)
X1 = Comp1(Ke=0.1, Ka=1, DAT2)
X1
matplot(DAT2[, "TIME"], X1, type="l")
```

 DAT

An Example of Dosing History Table

Description

This is a conventional NONMEM input data format.

Usage

DAT

Format

This data frame has 5 columns with 18 time-points for the simulation.

TIME Time

AMT Amount given for the compartment of CMT column

RATE Infusion rate

CMT Compartment number, 1=gut, 2=central, 3=peripheral, etc.

DV Currently blank and not used.

Details

To be used at Comp1 or nComp, expand dosing history with ExpandDH function.

dx	<i>Simplest diagnostic plot for minimization result</i>
----	---

Description

It performs a simple diagnostic plot from the result of `nlr`.

Usage

```
dx(r)
```

Arguments

`r` a result from `nlr` or `wn15`

Details

This plots 'Observation vs. Prediction' and 'Normalized Residual vs. Prediction' only. Normalized residual are meant to be distributed as standard normal distribution, $N(0, 1)$.

Value

This just draws a plot.

Author(s)

Kyun-Seop Bae jsk@acr.kr.i

ExpandDH	<i>Expand Dosing History Table</i>
----------	------------------------------------

Description

It expands dosing history table.

Usage

```
ExpandDH(DH, Fo = 1)
```

Arguments

`DH` Dosing history table of NONMEM type
`Fo` Bioavailability of the first (gut) compartment

Details

It expands dosing history table of conventional NONMEM data format. It calculate bioavailable amount, then add time points of non-differentiable, e.g. stopping points of infusion.

Value

Returns expanded dosing history table.

Author(s)

Kyun-Seop Bae `jsk@acr.kr.i`

Examples

```
DAT
ExpandDH(DAT) # One observation point is increased at the time of 27.
```

nComp

Get Amounts of Each Compartments using Lambdas and Coefficients of Multi-compartment Model

Description

It calculates using multi-compartment model.

Usage

```
nComp(Sol, Ka=0, DH)
```

Arguments

Sol	Solution list of lambdas and coefficients
Ka	Absorption rate constant
DH	Expanded dosing history table

Details

First compartment is the gut compartment for oral dosing. IV bolus and infusion dosing should be done at the second compartment. If a bolus dose was given at time T, it is reflected at times of larger than T. This is more close to real observation. ADAPT does like this, but NONMEM does not.

Value

This returns a table with the gut and the other compartment columns

Author(s)

Kyun-Seop Bae `jsk@acr.kr.i`

Examples

```
DAT
DAT2 = ExpandDH(DAT)
Sol = SolComp2(K10=0.1, K12=3, K21=1)
X2 = nComp(Sol, Ka=1, DAT2)
X2
matplot(DAT2[, "TIME"], X2, type="l")
```

nlr

*Nonlinear Regression in R***Description**

It performs nonlinear regression usually for pharmacokinetic and pharmacodynamic models.

Usage

```
nlr(Fx, Data, pNames, IE, LB, UB, Error="A", ObjFx=ObjDef, SecNames, SecForms,
    Method="L-BFGS-B", Sx)
```

Arguments

Fx	Function for structural model. It should return a vector of the same length to observations.
Data	Data table which will be used in Fx. Fx should access this with <code>e\$DATA</code> .
pNames	Parameter names in the order of Fx arguments
IE	Initial estimates of parameters
LB	Lower bound for <code>optim</code> function. The default value is 0.
UB	Upper bound for <code>optim</code> function. The default value is <code>1e+06</code> .
Error	Error model. One of "A" for additive error, "POIS" for Poisson error, "P" for proportional error, "C" for combined error model, "S" for general error model. With Error="S", Sx should be provided.
ObjFx	Objective function to be minimized. The default is maximum likelihood estimation function(-2 log likelihood).
SecNames	Names of secondary parameter estimates
SecForms	Formula to calculate the secondary parameter estimates
Method	"L-BFGS-B" is default. See <code>optim</code> for more detail.
Sx	Scale function. This is usually the inverse of weight. It should return the same length(nrow) of Y. When Error="S", Scale function should be provided as Sx.

Details

This uses scaled transformed parameters and environment `e` internally.

Value

Est	Point estimate(PE) with standard error(SE) and relative standard error(RSE)
Cov	Variance-covariance matrix of the objective function at the value of point estimates
run\$m	Count of positive residuals
run\$n	Count of negative residuals
run\$run	Count of runs of residuals
run\$p.value	P value of run test with excluding zero points

Objective Function Value

	Minimum value of the objective function
-2LL	-2 times log likelihood
AIC	Akaike Information Criterion
AICc	Corrected Akaike Information Criterion
BIC	Schwarz Bayesian Information Criterion
Convergence	Convergence code from <code>optim</code>
Message	Message from <code>optim</code> .
Prediction	Fitted(predicted) values
Residuals	Residuals
Scale	Scales with Error="S". Variances for each points are scale vector multiplied by <code>ScaleErrVar</code> in <code>Est</code> .
Elapsed Time	Consumed time by minimization

Author(s)

Kyun-Seop Bae jsk@acr.kr

Examples

```
tData = Theoph
colnames(tData) = c("ID", "BWT", "DOSE", "TIME", "DV")

fPK = function(THETA) # Prediction function
{
  DOSE = 320000 # in microgram
  TIME = e$DATA[, "TIME"] # use data in e$DATA

  K    = THETA[1]
  Ka   = THETA[2]
  V    = THETA[3]

  P = DOSE/V*Ka/(Ka - K) * (exp(-K*TIME) - exp(-Ka*TIME))
  return(P)
}

IDs = unique(tData[, "ID"])
nID = length(IDs)
for (i in 1:nID) {
  Data = tData[tData$ID == IDs[i],]
  Res = nlr(fPK, Data, pNames=c("k", "ka", "V"), IE=c(0.1, 3, 500),
            SecNames=c("CL", "Thalf", "MRT"), SecForms=c(~V*k, ~log(2)/k, ~1/k))
  print(paste("## ID =", i, "##"))
  print(Res)
}
```

Secondary

Get Secondary Parameter Estimates

Description

Get standard error and relative standard error (cv) of the secondary parameter estimate

Usage

```
Secondary(Formula, PE, COV)
```

Arguments

Formula	Formula to calculate the secondary parameter estimate
PE	Point estimates of primary parameters with names
COV	Variance-covariance matrix of primary estimates

Details

Variables within `Formula` should exist in the names of `PE` vector.

Value

This returns point estimate, standard error, relative standard error of the secondary parameter estimate.

Author(s)

Kyun-Seop Bae jsk@acr.kr

Examples

```
tData = Theoph
colnames(tData) = c("ID", "BWT", "DOSE", "TIME", "DV") # Table requires DV column

fPK = function(THETA) # Prediction function
{
  AMT = 320000 # in microgram
  TIME = e$DATA[, "TIME"]
  V = THETA[1]
  K = THETA[2]
  Ka = THETA[3]
  Cp = AMT/V*Ka/(Ka - K)*(exp(-K*TIME) - exp(-Ka*TIME))
  return(Cp)
}
Data = tData[tData$ID == 1,]
Res = nlr(fPK, Data, pNames=c("V", "K", "Ka"), IE=c(30000, 0.1, 2))
Secondary(~V*K, Res$Est["PE", 1:e$nPara], Res$Cov)
```

SolComp2*Get Lambdas and Coefficients of Two-compartment Model*

Description

It calculates lambdas and coefficients for two-compartment model from K10, K12, and K21.

Usage

```
SolComp2(K10, K12, K21)
```

Arguments

K10	Ke, Elimination rate constant from central compartment
K12	Rate constant from the central to the peripheral compartment
K21	Rate constant from the peripheral to the central compartment

Details

It calculates lambdas and coefficients of two-compartment model from K10, K12, and K21. Lambdas should have no identical values.

Value

This returns a list of lambdas and coefficients.

Author(s)

Kyun-Seop Bae jk@acr.kr.i

Examples

```
DAT
DAT2 = ExpandDH(DAT)
Sol = SolComp2(K10=0.1, K12=3, K21=1)
X2 = nComp(Sol, Ka=1, DAT2)
X2
matplot(DAT2[, "TIME"], X2, type="l")
```

SolComp3*Get Lambdas and Coefficients of Three-compartment Model*

Description

It calculates lambdas and coefficients for three-compartment model from K10, K12, K21, K13, and K31.

Usage

```
SolComp3(K10, K12, K21, K13, K31)
```

Arguments

K10	Ke, Elimination rate constant from central compartment
K12	Rate constant from the central to the first peripheral compartment
K21	Rate constant from the first peripheral to the central compartment
K13	Rate constant from the central to the second peripheral compartment
K31	Rate constant from the second peripheral to the central compartment

Details

It calculates lambdas and coefficients of two-compartment model from K10, K12, and K21. Lambdas should have no identical values.

Value

This returns a list of lambdas and coefficients.

Author(s)

Kyun-Seop Bae `jk@acr.kr`

Examples

```
DAT
DAT2 = ExpandDH(DAT)
Sol = SolComp3(K10=0.1, K12=3, K21=1, K13=2, K31=0.5)
X3 = nComp(Sol, Ka=1, DAT2)
X3
matplot(DAT2[, "TIME"], X3, type="l")
```

wnl5

Old type WinNonlin - Least Square not MLE

Description

It performs old type Winnonlin regression.

Usage

```
wnl5(Fx, Data, pNames, IE, LB, UB, Error="A", ObjFx=ObjLS)
```

Arguments

Fx	Function for structural model. It should return a vector of the same length to observations.
Data	Data table which will be used in Fx. Fx should access this with <code>e\$DATA</code> .
pNames	Parameter names in the order of Fx arguments
IE	Initial estimates of parameters
LB	Lower bound for <code>optim</code> function. The default value is 0.
UB	Upper bound for <code>optim</code> function. The default value is <code>1e+06</code> .
Error	Error model. One of "POIS" for Poisson error, "P" for proportional error, and others for additive error model.
ObjFx	Objective function to be minimized. The default is least square function.

Details

This uses scaled transformed parameters and environment `e` internally. Here we do not provide standard error. If you want standard error, use `nlr`.

Value

PE	Point estimates
WRSS	Weighted Residual Sum of Square
run\$m	Count of positive residuals
run\$n	Count of negative residuals
run\$run	Count of runs of residuals
run\$p.value	P value of run test with excluding zero points
Objective Function Value	
	Minimum value of the objective function
AIC	Akaike Information Criterion
SBC	Schwarz Bayesian Information Criterion
Condition Number	
	Condition number
Message	Message from <code>optim</code> .
Prediction	Fitted(predicted) values
Residuals	Residuals
Elapsed Time	Consumed time by minimization

Author(s)

Kyun-Seop Bae jk@acr.kr

Examples

```
tData = Theoph
colnames(tData) = c("ID", "BWT", "DOSE", "TIME", "DV")

fPK = function(THETA) # Prediction function
{
  DOSE = 320000 # in microgram
  TIME = e$DATA[, "TIME"] # use data in e$DATA

  K = THETA[1]
  Ka = THETA[2]
  V = THETA[3]
  Cp = DOSE/V*Ka/(Ka - K)*(exp(-K*TIME) - exp(-Ka*TIME))
  return(Cp)
}

IDs = unique(tData[, "ID"])
nID = length(IDs)
for (i in 1:nID) {
  Data = tData[tData$ID == IDs[i],]
  Res = wnl5(fPK, Data, pNames=c("k", "ka", "V"), IE=c(0.1, 3, 500))
  print(paste("## ID =", i, "##"))
  print(Res)
}
```

Index

- *Topic **Diagnostic Plot**
 - dx, [5](#)
- *Topic **Dosing history**
 - ExpandDH, [5](#)
- *Topic **Least Square Estimation**
(Old WinNonlin)
 - wnl5, [11](#)
- *Topic **Maximum Likelihood Estimation**
 - nlr, [7](#)
- *Topic **Model Comparison**
 - cmpChi, [3](#)
- *Topic **Multi-compartment**
 - nComp, [6](#)
- *Topic **One compartment**
 - Comp1, [3](#)
- *Topic **Packages**
 - wnl-package, [2](#)
- *Topic **Secondary**
 - Secondary, [9](#)
- *Topic **Three-compartment**
 - SolComp3, [10](#)
- *Topic **Two-compartment**
 - SolComp2, [10](#)
- *Topic **datasets**
 - DAT, [4](#)

cmpChi, [3](#)
Comp1, [3](#)

DAT, [4](#)
dx, [5](#)

ExpandDH, [5](#)

nComp, [6](#)
nlr, [7](#)

Secondary, [9](#)
SolComp2, [10](#)
SolComp3, [10](#)

wnl (wnl-package), [2](#)
wnl-package, [2](#)
wnl5, [11](#)